

ITEM Harris Cutting Nozzle				
Model Size	6290 Thickness For Acetylen	Orifice	6290NX Thickness For LPG Gas	Orifice
1	15-25	1.2	15-25	1.2
2	25-50	1.6	25-50	1.6
3	50-100	2	50-75	2
4	100-175	2.4	75-150	2.4



ITEM Victor Cutting Nozzle				
Model Size	1-101 Thickness	Orifice	GPN Thickness	Orifice
1	10-20	1.2	10-20	1.2
2	20-40	1.5	20-40	1.6
3	40-60	1.8	40-60	2
4	60-80	2.1	60-80	2.4



EQUIPOS DE CORTE TIPO HARRIS Y TIPO VICTOR

SKU	Gas	Máx. presión de entrada	Conexión de entrada	Manómetros de 2-1/2" Entrada	Manómetros de 2-1/2" Salida
NXT-LXR-	Oxígeno	3000 PSIG	CGA-540	0-4000 PSIG	0-200 PSIG
NXT-LXR-	Acetileno	400 PSIG	CGA-510	0-400 PSIG	0-30 PSIG
NXT-LXR-	Butano y/o Propano	400 PSIG	CGA-510	0-400 PSIG	0-30 PSIG



CONECTORES RAPIDOS HEMBRA Y MACHO



DESCRIPTION	NXT-CC20 Cable Connectors
TYPE	70-95, Male(plug)
	70-95, Female(socket)

PINZA DE TIERRA

Standard ground clamps have a spring at the pivot point of the handle to hold the clamp in place. The quick action handle provides fast clamping to flat and round surfaces.



Current (Maximum)	Compatible Cable Gauge Range	Jaw Opening (Maximum)	Throat Depth	Material	Code
300 A	2 AWG to 1/0 AWG	2 in	3-1/4 in	Steel	NXT-GC-300
500 A	1/0 AWG to 3/0 AWG	2 in	3-3/8 in	Steel	NXT-GC-500

PORTAELECTRODO

The jaws on these clamp-style electrode holders (also known as tong-style electrode holders) grip electrodes tightly and release with a squeeze of the handle for quick electrode changes. The holders let welding operators control the position of the electrode during stick welding tasks. They connect to a stick welder that supplies current to the electrode.



Maximum Amperage	For Maximum Electrode Diameter	Wire Gauge	Duty Rating	Duty Rating	Holder Jaw Material	Cable Connection Type	Code
300 A	5/32 in	2/0	Heavy Duty	Heavy Duty	Copper Alloy	Ball Point Screw	NXT-EHL-300
500 A	7/32	2/0	Heavy Duty	Heavy Duty	Copper Alloy	Ball Point Screw	NXT-EHL-500